


# PATENT SPECIFICATION (11) 1 565 178

1 565 178 (21) Application No. 6060/78 (22) Filed 15 Feb. 1978  
 (31) Convention Application No. 9179/77 (32) Filed 24 Feb. 1977 in  
 (33) Australia (AU)  
 (44) Complete Specification Published 16 Apr. 1980  
 (51) INT. CL.<sup>3</sup> F16B 35/00 // 25/00  
 (52) Index at Acceptance  
 F2H 11A6A 11A6D1 11A6E1



## (54) BONE SCREW

(71) We, INTERFIX LIMITED, a Company incorporated under the Laws of Hong Kong, C/-Johnson, Stokes & Master, Alexandra House, 16/20 Chater Road, Hong Kong, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:-

This invention relates to bone screws; that is, those surgical fastenings by which two pieces of bone may be held together. Although usable in many forms of bone connection, bone screws of the kind under consideration, while not restricted thereto, are particularly useful in cross fixation of fractured or severed bone fragments.

In almost all bone connections of the kind under consideration, it is essential for the fractured surfaces to be united to be brought into closely contacting mutual confrontation. This intimacy of contact is usually referred to as "compression". The actual need is for the fractured surfaces to be in close, well-fitting contact and to be so held during the healing process. In practice, the simplest way of ensuring this close contact is, where practicable, to apply a compressive loading to the bone portions in a direction substantially normal to the fracture faces.

Hitherto, standard bone screws have been of two typical forms. One of these has a thread only at its leading end, the head at the trailing end being separated from the thread by a smooth, cylindrical shank. It will be clear that such a bone screw, by threading wholly in the remote bone fragment and extending freely through the near fragment, can provide compressive action upon the fractured faces to be united.

The second type of bone screw has a stem or shaft threaded over its full length. Such a screw can only be used to apply compression between two bone fragments if the near

fragment is "over drilled" so that the thread engages solely in the remote fragment, the near fragment being free to move over the stem of the screw during insertion.

In both these cases it will be clear that this gaining of compressive action is achieved at the expense of subjecting the bone surface immediately below the screw head to concentrated bearing loads, and also at the expense of the screw head constituting a relatively large protrusive element.

It is not uncommon for the standard type of bone screw to be used with washers or other metallic inserts between the screw head and the adjacent bone surface. Any such inclusions are likely to provide some degree of load spreading which would relieve bearing stress intensity on the bone surface. But this load spreading facility is often insufficient because bone surfaces are very rarely flat and even where a washer or other insert is provided (unless specially moulded closely to fit the bone), the bearing pressure exerted by the screw head remains, in effect, a highly concentrated load and crumbling or other failure of the adjacent bone affected frequently occurs without sufficient compressive action at the fractured faces being achieved.

The standard type of bone screw has several other shortcomings. For example, the near bone fragment is held relative to the remote portion purely by compressive forces which act in the line of the screw; the screw head merely abutting the cortical surface of the near fragment as distinct from being firmly and securely anchored to that fragment. If the cortical bone layer directly under the screw head provides inadequate support either during insertion or subsequently, then compression is lost and the near bone fragment is free to move relative to the trailing part of the screw. In consequence, relative movement between the bone portions to be held can occur.

A further adverse factor is that of bone resorption. This may be a physiological response to localised pressure and may occur either directly under the screw head or at the fracture site. Clearly, where such resorption occurs, loosening of the screw may also arise, with subsequent movement of the bone fragments.

The object of this invention is to overcome or ameliorate the shortcomings indicated above in a very simple but highly effective manner.

The invention provides a screw for use in connecting a fractured portion of a bone to its parent bone comprising:

- (a) a shaft comprising a leading end portion, a trailing end portion, and a central unthreaded portion;
- (b) a first uniformly pitched screw thread on said leading end portion;
- (c) a second uniformly pitched screw thread on said trailing end portion which, relative to said first screw thread, is like-handed but of different pitch, and
- (d) means on the trailing end of said trailing portion to accommodate a tool for driving the screw, said screw being characterized in that (i) said central portion spaces said end portions apart and is axially longer than either of them; (ii) said second thread extends radially wholly beyond the circumference of said central portion, and the crest diameter of said second thread is greater than the diameter of any other part of said screw, thereby to adapt said screw for entire encasement within the bone portions to be connected thereby, and (iii) both of said threads are adapted to thread in the cancellous material of the respective bone portions to be joined by said screw.

Far more usually, screws according hereto will be required to provide compressive action as referred to above; and this being so, the pitch of the first or leading end screw-thread will slightly exceed that of the second or trailing end thread. In some situations in orthopaedic surgery, it may be desired to apply distraction between two bone fragments as distinct from compressive action as referred to above. The screws hereof may be suited to this distraction purpose by making the pitch of the trailing end thread greater than that of the leading end thread.

Examples of the invention are illustrated in the drawings herewith. All of the figures are drawn on an over-sized scale.

Figure 1 is a side elevation, half in section, of a compression bone screw.

Figure 2 is a similar view of a distraction bone screw.

Figure 3 is a plan projected from Figure 2.

Figure 4 is a side elevation, half in section, of a cannulated, compression bone screw.

Figure 5 is a plan projected from Figure 4.

Referring to Figure 1 the shaft of the screw comprises leading end portion 6 and a trailing end portion 7 axially spaced apart by a substantially cylindrical shank 8. The leading end portion is furnished with first screw thread 9 and the trailing end portion has a second screw thread 10. The threads 9 and 10 are like-handed. This screw is intended to be one for applying compressive action, hence the pitch of thread 9 is slightly greater than that of thread 10. As will be seen from Figure 1, the trailing end of the bone screw is furnished with a transverse slot 11 to which a screw driver or the like may be applied.

The screw illustrated in Figure 1 is intended principally to engage the cancellous or spongy inner tissue of a bone. Accordingly, both of its threads are of a form which may be described as acutely backed buttress type; in that the thread helices have pressure faces 12 and 13 which are substantially normal to the longitudinal axis of the screw and backing surfaces 14 and 15, which are relatively acute. It will be noticed from the drawing that the bearing faces 12 and 13 are in mutually confronting disposition, so as to provide, as much as possible, bone loading forces parallel to the longitudinal axis of the screw. It will be understood however, that the invention is in no way limited to this or any other thread form.

In using a screw according hereto it is first necessary to select a screw length suited to the task in hand. An entry bore of diameter approximately equal to the root diameter of trailing end portion 7 and able freely to accept shank 8 is drilled into the near bone fragment to a sufficient depth to accommodate that portion and shank 8. A bore of diameter approximately equal to the root diameter of leading end portion 6 is then drilled coaxially with the first mentioned bore through the near bone fragment, through the fracture inter-face and into the remote bone fragment; the drilling into the remote bone fragment being of a depth to accept the screw leading end portion 6. Before the screw is inserted, the second mentioned bore is preferably tapped with a tap suitable for the thread on leading end portion 6.

When engagement is established, continued turning of the screw will tend to cause the leading end of the screw to advance axially into the remote fragment to a slightly greater extent than it does relative to the near fragment. This puts the screw in tension and hence the fracture faces under compression.

It will be appreciated that an important aspect of the present invention resides in the absence of a conventional head on the trailing end portion 2. This is valuable in many situations of bone screw use because

70 screw head protrusion is avoided; and the threaded trailing end of the screw can be wholly sunken into the bone tissue. This in turn allows, for example, the screw to be inserted through the cartilage of a joint surface and buried beneath that surface so that the joint and its use would be unaffected by the presence of the bone screw. In other words, where hitherto a bone screw could not be applied through cartilage owing to the protrusive presence of a screw head within the joint, a screw according to the present invention may be effectively used in that location without impairing resumption of the normal joint relationship and without break or hindrance to full re-establishment of the cartilage over the rubbing surfaces of the joint.

85 The screw shown in Figures 2 and 3 is virtually the same as that shown in Figure 1 except for the leading end portion 6a having a thread 9a whereof the pitch is slightly less than that of the thread 10a of the trailing end portion 7a. Hence this screw is a distraction screw; that is, one which, when tightened tends to hold the joined bone fragments slightly spaced apart or at least not firmly pressed each towards the other.

90 The screw shown in Figures 4 and 5 is virtually the same as that shown in Figure 1 except for being provided with a cannula or lumen 16 to provide for use of a guide wire in those cases where such is required. This embodiment also illustrates the provision of a hexagonal well 17, to receive a key spanner, instead of a screw driver slot such as that shown, at 11, in Figure 1.

#### WHAT WE CLAIM IS:

- 105 1. A screw for use in connecting a fractured portion of a bone to its parent bone, comprising:
- 110 (a) a shaft comprising a leading end portion, a trailing end portion, and a central unthreaded portion;
- 115 (b) a first uniformly pitched screw thread on said leading end portion;
- (c) a second uniformly pitched screw thread on said trailing end portion which, relative to said first screw thread, is like-handed but of different pitch, and
- 120 (d) means on the trailing end of said trailing portion to accommodate a tool for driving the screw, said screw being characterised in that:
- 125 (i) said central portion spaces said end portions apart and is axially longer than either of them,
- (ii) said second thread extends radially wholly beyond the circumference of said central portion, and the crest diameter of said second thread is greater than the diameter of any other part of said screw, thereby to adapt said screw for entire encasement within the bone portions to be connected thereby and
- 130

(iii) both of said threads are adapted to thread in the cancellous material of the respective bone portions to be joined by said screw.

2. A bone screw according to Claim 1, wherein the pitch of said first screw thread is greater than that of said second screw thread.

3. A bone screw according to Claim 1 wherein the pitch of said first screw thread is less than that of said second screw thread.

4. A bone screw according to any one of the preceding claims, wherein said shaft has a cannula extending through its axial length.

5. A bone screw substantially as herein described with reference to Figure 1 or Figures 2 and 3 or Figures 4 and 5 of the drawings herewith.

For the Applicant:-  
F.J. CLEVELAND & COMPANY,  
Chartered Patent Agents,  
40/43 Chancery Lane,  
London WC2A 1JQ.

Printed for Her Majesty's Stationery Office,  
by Croydon Printing Company Limited, Croydon, Surrey, 1980.  
Published by The Patent Office, 25 Southampton Buildings,  
London, WC2A 1AY, from which copies may be obtained.

1565178

COMPLETE SPECIFICATION

1 SHEET

This drawing is a reproduction of  
the Original on a reduced scale

